

delmatic metro touchpad

The **touchpad** provides user control and adjustment of lighting and lighting scenes, as well as other services including audio-visual functions, window blinds and temperature set-point: an integral sensor measures the room temperature at desk level avoiding the need for wall-mounted sensors.

The **touchpad** combines a precision cast aluminium body with glass 3.5" LCD display, stand-by mode with wake-up button, and integral USB charging port.

The **touchpad** incorporates context-sensitive graphical screens to provide intuitive operation and a wide choice of software configurable functions.

The **touchpad** transmits infra-red data to a ceiling-mounted **multisensor**. The multisensor enhances overall control through its integral motion detector (configurable for presence or absence detection) and photocell sensor which add presence-related control & daylight-linking to the overall control package.



touchpad

product ref: 116B2

features

- 3.5" LCD touchscreen
- Real-time lighting level, temperature & set-point display
- Integral room temperature sensor
- Infra-red communication avoids buswires & installation
- Internal rechargeable battery
- USB charging port
- Software configurable through USB port



dimensions

width	110 mm
depth	95 mm
height	35 mm

multisensor

The **touchpad** transmits infra-red data and commands to a ceiling-mounted **multisensor**.

The multisensor enhances energy-efficiency through its integral motion detector (configurable for presence or absence detection) and photocell sensor which add presence-related control of lighting and HVAC & daylight-linking to the overall control package.



multisensor

delmatic
www.delmatic.com

London, UK
+44 (0) 20 8987 5900
delmatic@delmatic.com

Dubai, UAE
+971 (0) 4 2566 722
sales@delmaticarabia.ae

Doha, Qatar
+974 4452 8226
sales@delmaticqatar.com

Riyadh, Saudi Arabia
+966 (0)1 211 8170
sales@delmaticsaudi.com